ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

C E R T I F I C A T E

No. Z1 091172 0024 Rev. 01

Holder of Certificate: **CAGSAN MERDIVEN VE ERISIM EKIPMANLARI SANAYI TICARET LIMITED SIRKETI**
Dilovasi O.S.B. 3 Kisim Meriç Cad. 1
41455 MUALLIM KÖYÜ - GEBZE, KOCAELI
TÜRKIYE

Certification Mark:

Product: **Platform ladders (for professional use)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier.
All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: MES200220001135A00TR

Valid until: 2029-05-21
Date, 2024-05-24

(Andrea Rotundo)

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

C E R T I F I C A T E

No. Z1 091172 0024 Rev. 01

Model(s): **TP200, TP250; KPN3: KPN4; KPN5; KPN6; KPN7; KPN8; KPN9; KPN10; KPN11; KPN12; KPN13; KPN14; VX4-5; VX5-7; VX7-10.**

Brand Name: **CAGSAN**

Parameters:

Model	No. of steps	Max. platform height [cm]	Dead load [kg]
TP200	5x2	200	38,0
TP250	6x2	250	41,8

Stile [mm] : 70x27,6x2,5 – 64x25x1,25
Stile Material : EN AW-6063

Rung [mm] : 30x30x1,4
Rung Material : EN AW-6063-T5

Model	No. of steps	Max. platform height [cm]	Dead load [kg]
KPN3	4	100	25,0
KPN4	5	125	26,6
KPN5	6	150	28,2
KPN6	7	175	29,8
KPN7	8	200	31,4
KPN8	9	225	33,0
KPN9	10	250	34,6
KPN10	11	275	36,2
KPN11	12	300	37,8
KPN12	13	325	39,4
KPN13	14	350	41,0
KPN14	15	375	42,6

Stile [mm] : 104,5x28,8x2,20
Stile Material : EN AW-6063

Rung [mm] : 103,8x30x2,0 Rung Material: : EN AW-6063
Platform Material : EN AW 1050 Aluminium Sheet (thickness=3 mm)

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

C E R T I F I C A T E

No. Z1 091172 0024 Rev. 01

Model	No.of rungs	Max. Platform Heigt [cm]	Max. External Dimensions (mm)	Dead load [kg]
VX4-5	4	130	850x2360x438	28
VX5-7	5	183	850x2640x438	31
VX7-10	7	261	850x3200x438	36

Stile [mm] : 63,5x25x1,25
Stile Material : EN AW-6063

Rung [mm] : 30x30x1,8
Rung Material: : EN AW-6063

Products are conform to Swedish requirement listed in Annex A (A-deviations) of EN 131-1:2015+A1:2019

Tested according to:

EN 131-1:2015/A1:2019
EN 131-2:2010/A2:2017
EN 131-3:2018
EN 131-7:2013
EK5/AK1 15-06:2015

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®