CERTIFICADO ◆ 인증서 ◆ CERTIFICATO ◆ 認証書 ◆ CERTIFICATE ◆ 认证证书 ◆ ZERTIFIKAT

C E R T I F I C A T E

No. Z1 091172 0023 Rev. 01

Holder of Certificate: **CAGSAN MERDIVEN VE ERISIM EKIPMANLARI SANAYI TICARET LIMITED SIRKETI**
Dilovasi O.S.B. 3 Kisim Meriç Cad. 1
41455 MUALLIM KÖYÜ - GEBZE, KOCAELI
TÜRKIYE

Certification Mark:

Product: **Scaffold (mobile working tower)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier.
All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: MEC-V200220021570A-000TR

Valid until: 2031-07-15

Date, 2026-07-16

(Luca Pitti)

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

C E R T I F I C A T E

No. Z1 091172 0023 Rev. 01

Model(s):

Serie TeleSAFE
TeleSAFE_S004_XLN;
TeleSAFE_S005_XLN;
TeleSAFE_S006_XLN;
TeleSAFE_S007_XLN;
TeleSAFE_S008_XLN;
TeleSAFE_S004_XLN_PR;
TeleSAFE_S005_XLN_PR;
TeleSAFE_S006_XLN_PR;
TeleSAFE_S007_XLN_PR;
TeleSAFE_S008_XLN_PR.

Serie ALL FLEX
ALL FLEX 0;
ALL FLEX A3;
ALL FLEX A4;
ALL FLEX A5;
ALL FLEX A6.

Brand Name: **CAGSAN**

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

C E R T I F I C A T E

No. Z1 091172 0023 Rev. 01

Parameters:

Serie Tele SAFE

Frame, platfrom and rung material: EN AW 6060 T6, EN AW 6063
Platform material: EN 636 Class E80 F40 – Plywood (thickness=12 mm)
Group according to EN 1004-1:2020: 3
Max.loading capacity : 2,0 kN/m^2

Model	Approx.max dimensions [m] [LxWxH]	Approx.max.dead load [kg]
TeleSAFE_S004_XLN	2,12 x 1,9 x 3,91	98
TeleSAFE_S005_XLN	2,12 x 1,9 x 4,99	120
TeleSAFE_S006_XLN	2,12 x 1,9 x 5,58	124
TeleSAFE_S007_XLN	2,12 x 1,9 x 6,39	128
TeleSAFE_S008_XLN	2,17 x 2,1 x 7,23	168
TeleSAFE_S004_XLN_PR	2,12 x 1,9 x 3,91	93
TeleSAFE_S005_XLN_PR	2,12 x 1,9 x 4,99	115
TeleSAFE_S006_XLN_PR	2,12 x 1,9 x 5,58	119
TeleSAFE_S007_XLN_PR	2,12 x 1,9 x 6,39	123
TeleSAFE_S008_XLN_PR	2,17 x 2,1 x 7,23	162

C E R T I F I C A T E

No. Z1 091172 0023 Rev. 01

Serie ALL FLEX

Model	Approx.max.dead load [kg]	Approx.dimensions [m]
ALL FLEX 0	37	2,13 x 1,75 x 0,8
ALL FLEX A3	56	2,13 x 2,19 x 1,51
ALL FLEX A4	81	3,25 x 2,95 x 2,83
ALL FLEX A5	89	4,09 x 2,95 x 2,83
ALL FLEX A6	117	5,21 x 2,95 x 2,83

Rung profile [mm]: 30 x 30 x 1,4
Material : EN AW-6060, EN AW-6063

Stile profile [mm]: 75 x 25 x 1,2
Material : EN AW-6060, EN AW-6063

Platform [mm] : 600 x 1746 x 87
Frame material : EN AW-6060, EN AW-6063

Tested according to: EN 1004-1:2020
EN 1004-2:2021
PPP 52015D:2022

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany